

SUMMARY

The Plastial G3 is a high performing downlight ideal for commercial and residential applications. Engineered to deliver high lumen efficacy, this downlight incorporates an integrated dimmable driver. Rated to IC-4, this downlight can be safely installed under ceiling insulation.



| | | | |
|--|--|--|---|
| | | | <ul style="list-style-type: none"> VEET Approved IPART Approved |
|--|--|--|---|

PRODUCT DATA

| | |
|-----------------|--|
| Order Code | 173353 |
| Voltage | 220-240V |
| Wattage | 7W |
| Lumen Output 3K | 750Lm |
| CCT | 3000K |
| IP Rating | IP54 |
| IC Rating | IC-4 |
| Beam Angle | 100° |
| Light Source | SMD Chips |
| Driver | Integrated |
| Dimmable | Yes. Leading or Trailing Edge, Universal (Refer to Dimmer Compatibility List) |
| Connection | 1.2 flex & plug |
| Fitting Type | Recessed |
| Cutout Size | Ø90mm |
| Construction | Polycarbonate body / opal polycarbonate diffuser |
| Fitting Colour | White |
| PF | 0.9 |
| Net Weight (kg) | 0.20 |
| Lifetime L70B50 | 35,000 hours |
| Warranty | 5 years |

