

Features

- Even light output
- High efficiency SMD LED chips
- Powder coated steel base
- Opal high quality diffuser
- 6mm terminal block
- Centred cable entry
- Compatible with 51mm Beza box
- Plug and play modular sensor and emergency kit install on-site

Dimming Options





- Trailing and Leading Edge
- Universal

Includes

- Constant current dimmable LED driver
- Mounting accessories

Applications

Residential, hallways, stairwells, porches, walls and ceilings



Product Data

Order Code	Wattage	CCT	Lumen Output	Beam Angle	PF	Lifetime L70B50	Weight
181008	12W	3000K/4000K/5700K	1250/1300/1300Lm	120°	0.9	35000h	0.33
181003	14W	3000K/4000K/5700K	1300/1500/1400Lm	120°	0.9	35000h	0.54
181004	17W/27W	3000K/4000K/5700K	1450/1600/1500lm 2300/2500/2400lm	120°	0.9	35000h	0.75

Note: Voltage 220-240V. Operating Temperature: -20 °C~+40 °C. Operating Frequency=50/60Hz.

Optional Accessories

Description & Order Codes

Microwave motion sensor kits 283059. Sustained emergency kits 283049



Microwave motion sensor kits



Sustained emergency kits (LiFePO4 Battery)