

SUMMARY

The Legolite is a low glare UGR<19 commercial downlight solution engineered to deliver high lumen efficacy. With Tri-Colour and Multi-Watt selectable technology, it offers the flexibility and convenience of 3 colour temperatures and 2 wattages in 1 fitting, allowing installers to cater to a broader range of needs with fewer variants. It featuring a faceted reflected and a transparent lens for superb optics. With the installer in mind, the Legolite incorporates an integrated dimmable driver and a pre-wired flex and plug for quick and easy installation.



			<p>✓ VEET Approved</p> <p>✓ IPART Approved</p>
--	--	--	--

PRODUCT DATA

Order Code	263010	
Voltage	220-240V	
Wattage	Multi-Watt Selectable	
	25W	18W
Lumen Output 3K	2150Lm	1650Lm
Lumen Output 4K & 5K	2300Lm	1800Lm
CCT	Tri-Colour Selectable - 3K / 4K / 5K	
IP Rating	IP54	
UGR Rating	UGR<19	
IC Rating	CA90	
Beam Angle	60°	
Light Source	SMD Chips	
Driver	Integrated	
Dimmable	Yes. Leading or Trailing Edge, Universal	
	(Refer to Dimmer Compatibility List)	
Connection	1.2m flex & plug	
Cutout Size	Ø200mm	
Construction	Polycarbonate body / opal polycarbonate diffuser	
Fitting Colour	White	
PF	0.9	
Net Weight (kg)	0.69	
Lifetime L70B50	50,000 hours	

