

## Features




- Die-cast aluminium
- Tempered glass cover
- High efficacy up to 160Lm/W
- DALI & 1-10V dimming options

## Applications

Industrial, Warehouses,  
Car Parks, Large Areas

## Warranty

5 years



## Product Data

| Order Code | Wattage | CCT   | Lumen Output | Beam Angle | Size (ØxH)mm | Weight (kg) |
|------------|---------|-------|--------------|------------|--------------|-------------|
| 273495     | 600W    | 5000K | 96000Lm      | 135*60°*   | 657x521x83   | 15.7        |
| 273494     | 600W    | 4000K | 96000Lm      | 135*60°*   | 657x521x83   | 15.7        |
| 273505     | 600W    | 5000K | 96000Lm      | 60°**      | 657x521x83   | 15.7        |
| 273504     | 600W    | 4000K | 96000Lm      | 60°**      | 657x521x83   | 15.7        |

[1] Operating temperature: -30°C~+45°C

[2] Voltage: 220-240V

[3] PF: 0.9

[4] \*: Asymmetric options: 110°20°/110°40°

[5] \*\*: Symmetric options: 15° / 30° / 45° / 60° / 90° / 120° / TYPE2 / TYPE3 / TYPE4

[6] Inrush Current: 240A@200µs

[7] Leakage Current ≥ 0.75mA

