



Features

- Type-3 distribution
- Rotatable lens
- Robust die-cast aluminum body
- High efficiency SMD LED chips
- Ingress protection: IP66
- Impact protection: IK08
- 5 year warranty



Applications

- Industrial
- Commercial
- Parking lots
- Large urban spaces



Products Data

Order Code	Wattage	CCT	Lumen Output	Beam Angle	Size(LxWxH)mm	Weight (KG)
463005	75W	5000K	11250Lm	Type III	428x247x55	3.45
463015	100W	5000K	15000Lm	Type III	428x247x55	3.45
463025	150W	5000K	22500Lm	Type III	428x247x55	3.45
463035	200W	5000K	30000Lm	Type III	458x268x55	6.90
463055	300W	5000K	45000Lm	Type III	458x268x55	6.90

[1] Voltage: 220~240V

[2] Operating Temperature: -30°C to +50°C

[3] PF:0.9

Note:

- **The Storm Area Light is supplied less slip fitter or u-bracket**
- **When ordering or specifying the Storm Area Light, a slip fitter or u-bracket must be added**

Optional Accessories

Item	Order Code
Photocell	463069
Slip Fitter	463079
U-Bracket 247	463119
U-Bracket 268 (200W)	463129
U-Bracket 325 (300W)	463139