

## BWP ECO LED Weatherproof Batten Gen 2

The high output LED weatherproof batten has longer life and the ability to select your preferred lumen output/wattage within one light fitting.

- Wide Polycarbonate body to cover old footprint
- Robust and lockable stainless steel clips on body
- Easy installation with large terminal block, stainless steel mounting clips, 20mm cable gland and one optional knock-out at the opposite end



### LUMEN SELECT™



80

CRI



IP65

Ingress  
Protection  
Rating



IK08

Impact Rating



5SDCM

MacAdam  
Steps



Non -  
Dimmable

Dimming



54,000hrs  
(L70/B50)

Lifetime



3 Years

Warranty



100°

Beam Angle


CODE	SYSTEM POWER	EXIT LUMEN	DIMENSIONS	WEIGHT	INRUSH CURRENT	LINE CURRENT	SENSOR TYPE
BWPECO202ECS	18W	2500lm 2100lm 2100lm	L655 x W130 x H92 mm	1kg	10.2A	0.08A	
BWPECO404ECSLS	40W 33W 27W 20W	5200lm 4200lm 3600lm 2500lm	L1265 x W130 x H92 mm	1.9kg	12.3A	0.19A	
BWPECO404ECSS	40W	4737lm 4600lm 4700lm	L1265 x W130 x H92 mm		3.4A	0.20A	Microwave
BWPECO505ECS	52W	5200lm 5900lm 5700lm	L1565 x W130 x H92 mm	2.5kg	12.7A	0.24A	

#### ACCESSORY CODE

#### DESCRIPTION

PRC05

REMOTE CONTROL FOR PROGRAMMING PIERLITE SENSORS (TYPE 05)



BWPECO202ECS



BWPECO404ECSLS, BWPECO404ECSS

Product Images



BWPECO404ECSLS, BWPECO404ECSS



BWPECO505ECS