



Features

- Multi-Watt selectable
- Tri-Colour selectable
- Die-casting aluminium trim
- Multiple cable entry points for easy installation
- Beza box compatible for easy installation
- Large 6mm terminal block for easy installation
- Even light distribution
- Fast connector
- Flicker-Free

Includes

- Mounting accessories

Installation Options

- Surface mounted

Applications

- Walkways
- Hallways
- Balconies
- Commercial
- Industrial

Warranty

- Five years for fitting

CERTIFICATION	IP RATING	DIMMABLE	TRI-COLOUR	Ra	DISTRIBUTION	DIMENSIONS(mm)	IK RATING

Order Code	Part No.	Model No.	Voltage	Watt.	PF	Color Temp.	Lumens	Beam Angle	Lifetime L70B50	Net Weight (kg)
281005	281005	BHD1-TC-D3022MN 10W	220-240V	10W	0.9	3000K/4000K/5000K	930/1000/1000lm	110°	50000h	1.28
		BHD1-TC-D3022MN 15W	220-240V	15W	0.9	3000K/4000K/5000K	1400/1500/1500lm	110°	50000h	1.28
		BHD1-TC-D3022MN 22W	220-240V	22W	0.9	3000K/4000K/5000K	1860/2000/2000lm	110°	50000h	1.28

[1] Operating Frequency=50/60Hz; [2] Operating Temperature:-30 °C ~+50 °C

Optional Accessories

Order Code	Part No.	Model No.	Description
283109	283109	ECD6BH BK71	Diecast Eyelid Cover for Fortlite Bunker Black
283049	283049	MA1EN04W005-L11W08	Sustained emergency kits
283059	283059	ECMMSB1	Microwave motion sensor kits