

SUMMARY

The Stellar V Wide is an IP20 batten ideal for the retrofit market in commercial and industrial applications. It features Five-Colour selectable and Multi-Watt selectable technologies, giving installers the choice of 5 colour temperatures and 3 wattages in 1 fitting so that fewer varieties are required to meet a broader range of needs. With the installer in mind, the Stellar V has been engineered with a clever toolless end cap and quick-to-fit single piece LED light module. It also incorporates multiple cable entry points and a large 6mm terminal block. The integrated sensor's dimming function can be conveniently controlled from a distance with the compatible remote control - available to order separately.



| | | | |
|--|--|--|--|
| | | | <p>✓ VEET Approved</p> <p>✓ IPART Approved</p> |
|--|--|--|--|

PRODUCT DATA

| | | | |
|----------------------------------|---|--------|--------|
| Order Code | 211025DS | | |
| Voltage | 220-240V | | |
| Wattage | Multi-Watt Selectable | | |
| | 20W | 14W | 10W |
| Lumen Output 3K | 1800Lm | 1260Lm | 900Lm |
| Lumen Output 4K, 5K, 5.7K & 6.5K | 2000Lm | 1400Lm | 1000Lm |
| CCT | Five-Colour Selectable - 3K / 4K / 5K / 5.7K / 6.5K | | |
| IP Rating | IP20 | | |
| Beam Angle | 120° | | |
| Light Source | SMD Chips | | |
| Driver | Integrated | | |
| Dimmable | Yes. 0-10V | | |
| Construction | Metal body / opal polycarbonate diffuser | | |
| Fitting Colour | White | | |
| PF | 0.9 | | |
| Net Weight (kg) | 1.54 | | |
| Lifetime L70B50 | 50,000 hours | | |
| Warranty | 5 years | | |

OPTIONAL ACCESSORIES

| ITEM | ORDER CODE |
|----------------|------------|
| Remote Control | 213979 |

