## MERCATOR



## Ikuü Smart Wi-Fi Dimmer Mechanism

## SSWM-DIM

## **Key Features:**

- Wi-Fi (No hub required)
- Press and hold for dimming
- LED indicator for on/off
- Terminals fit up to 3 x 1.5mm<sup>2</sup> building cables
- Compatible with most popular brands, 1, 2, or gang
- Trailing edge dimmer suits most of dimmable LED lights
- Indoor use only
- Approved to Australian and New Zealand electrical safety standards
- This dimmer is not suitable for use with non-dimmable, LED lights, ceiling exhaust, or sweep fans

Compliance Standards	AS/NZS 4268, AS/NZS 60669.1, AS/NZS 60669.2.1, CISPR 15, CISPR 32
Connectivity	Wi-Fi
Contact Material [Single Line Text Field]	Brass
Ip Rating	IP20
Material	Polycarbonate
Model	SSWM-DIM
Operating Load	Incandescent (Halogen)
Protocol	IEEE 802.11 b/g/n
Requirements	Existing 2.4GHz Wi-Fi network
Terminal Size [Single Line Text Field]	$3.5$ mm $^2$ (can fit up to $3 \times 1.5$ mm $^2$ wires per terminal)
Volt	250V
Warranty	3 years
Wireless Frequency	2.4GHz



