





Ikuü Smart Zigbee Rotary Dimmer Mechanism

SSWRM-ZB

Key Features:

- No neutral wire required
- Minimum 5W LED and incandescent loads
- Turn the dial for dimming; extra slim dial
- Terminals fit up to 3 x 1.5mm² building cables
- Compatible with most popular brands, 1, 2, or gang
- Trailing edge dimmer suits most of dimmable LED lights
- Indoor use only
- Approved to Australian and New Zealand electrical safety standards

Compliance Standards	AS/NZS 4268, AS/NZS 60669.1, AS/NZS 60669.2.1, AS/NZS 2772.2, CISPR 15, CISPR 32
Connectivity	Zigbee
Contact Material [Single Line Text Field]	Brass
Ip Rating	IP20
Material	Polycarbonate
Model	SSWRM-ZB
Operating Load	Incandescent (Halogen)
Protocol	IEEE 802.15.4
Requirements	Mercator Ikuü Zigbee hub
Terminal Size [Single Line Text Field]	3 x 1.5mm ²
Volt	250V
Warranty	3 years
Wireless Frequency	2.4GHz

One Clever App
 Easy. Seamless. Integrated
 Anywhere, anytime control
 Automate events
 Control device groups
 Schedule timers

works with
Hey Google

works with
alexa




IP20
 RATING


zigbee


DIMMER

3
 YEAR
 WARRANTY

Dimensions

40mm
 22mm
 EXT 60mm

