



## Walter 9W 90mm Ikuü Smart Zigbee RGB And CCT LED Downlight

## SMD4109W-RGB-ZB

- 9W LED downlight with Independent driver
- Zigbee 3.0 compliant
- Reliable and low latency
- Mesh technology for greater range
- IP44 rated (front face)
- 90mm cut-out
- IC-4 rated
- CCT control from warm white 3000K to daylight 5700K with App
- RGB mode for any colour, plus a variety of effects
- Lumen Efficacy 81lm/W
- Fitted with lead and plug
- On/Off and Dimmable with App
- Scheduling, Scenes and automation
- Network: 802.15.4 2.4GHz Requirements
- Mobile device running iOS or Android
- Refer to ikuu.com.au for minimum requirements.
- Existing 2.4 GHz WiFi network



## MERCATOR

Beam Angle	100°	
Colour Temperature	3000K-5700K+RGB	Anywhere, any time control
Cri	>80	Automate events Control device groups Schedule timers
Dimmable	Yes	
Globe Included	Yes	CHANGEABLE RGB LED
Globe Type	Integrated LED	DIMMABLE TEMPERATURE
Ip Rating	IP44	Dimensions
Lumens	740lm	Cut-out Ø92mm
Model	SMD4109W-RGB-ZB	
Warranty	3 Year	
Wattage	9W	25mm

— Ø110mm-