



## lkuü Smart Wi-Fi Light Dimmer Switch

## SSWD01G-WIFI

Key Features:

- Requires neutral
- Wi-Fi (no hub required)
- LED indicators: Blue for On, white for Pairing
- Terminals fit up to 3 x 2.5mm<sup>2</sup> building cables
- Retrofit to standard mounting bracket and accessories
- Gloss White, UV resistant material does not turn yellow
- Approved to Australian and New Zealand electrical safety standards

Compliance Standards	AS/NZS 4268, AS/NZS 60669.1, AS/NZS 60669.2.1, CISPR 15, CISPR 32		One Clever App Easy. Seamless. Integrated Anywhere, anytime control Automate events Control device groups
Connectivity	Wi-Fi	Roce Sorry Congre	Schedule timers
Contact Material [Single Line Text Field]	Brass	IP20 wif	
Ip Rating	IP20	RATING	
Material	Polycarbonate	Dimensions	
Model	SSWD01G-WIFI		13mm
Operating Load	Incandescent (Halogen)		
Protocol	IEEE 802.11 b/g/n	74mm	
Requirements	Existing 2.4GHz Wi-Fi network	115mm	31mm
Terminal Size [Single Line Text Field]	6mm <sup>2</sup> (can fit up to 3 x 2.5mm <sup>2</sup> wires per terminal	50mm	
Volt	250V		
Warranty	3 years		
Wireless Frequency	2.4GHz	── 73mm ──	

