



Ikuü Smart Zigbee Dimmer Mechanism

SSWM-DIMZ

Key Features:

- Zigbee 3.0 compliant
- No neutral wire required
- LED indicator for on/off
- Terminals fit up to 3 x 1.5mm² building cables
- Compatible with most popular brands, 1, 2, or gang
- Trailing edge dimmer suits most of dimmable LED lights
- Indoor use only
- This dimmer is not suitable for use with non-dimmable, LED lights, ceiling exhaust, or sweep fans
- Approved to Australian and New Zealand electrical safety standards

Compliance Standards	AS/NZS 4268, AS/NZS 60669.1, AS/NZS 60669.2.1, CISPR 15, CISPR 32
Connectivity	Zigbee
Contact Material [Single Line Text Field]	Brass
Ip Rating	IP20
Material	Polycarbonate
Model	SSWM-DIMZ
Operating Load	Incandescent (Halogen)
Protocol	IEEE 802.15.4
Requirements	Mercator Ikuü zigbee hub
Terminal Size [Single Line Text Field]	3.5mm ² (can fit up to 3 x 1.5mm ² wires per terminal)
Volt	250V
Warranty	3 years
Wireless Frequency	2.4GHz





One Clever App
Easy. Seamless. Integrated
Anywhere, anytime control
Automate events
Control device groups
Schedule timers




IP20
RATING

zigbee



DIMMER

3
YEAR
WARRANTY

Dimensions





