

# BES SERIES

## LED Exterior Surface Mounted Up/Down Wall Lights


### PRODUCT FEATURES

- Input voltage: 100-240V AC 50/60Hz
- Housing: aluminium
- Diffuser: glass
- Back plate: PC
- LED chips: 2pcs 5050
- Power factor: >0.5
- Ambient temp: -20 to 50°C
- Not suitable for use with dimmers
- Suitable for 2-way switching
- Suitable for use with PIR or Microwave sensors



 30,000hr Lifetime	 120° Beam Angle	<b>IP65</b> Rated	<b>3YEAR</b> Replacement Warranty
--	--	----------------------	---

Height: 174mm  
 Width of the TOP: 77mm  
 Depth of the TOP: 35mm  
 Width of the BOTTOM: 106mm  
 Depth of the BOTTOM: 51mm



PART NO.	DESCRIPTION	KELVIN (K)	LUMENS (LM)	WATT (W)	CRI	WEIGHT (KG)	BOX (CM)	CARTON QTY
BES1	WALL LED S/M Dark Grey Cone UP/Dn	3000	368	11	≥80	0.5	18.5x12.5x6.5	1/18
BES2	WALL LED S/M Matt WH Cone UP/Dn	3000	368	11	≥80	0.5	18.5x12.5x6.5	1/18