

# LED CANDLE LAMPS

## Product Features


- Input voltage 240V AC 50/60Hz
- Wattage: 4W
- 34pcs EDISON 3014 LED chips
- Life time: 30,000HRS(CAN2 & 8 are 25,000hrs)
- CRI: 80
- Aluminium cap base & heatsink
- Clear or frosted glass lamp cover
- Ambient temperature: -20~50°C
- Not suitable for dimming
- Can work with sensor



clear cover



frosted cover



CODE	DESCRIPTION	BASE	WATT (W)	KELVIN (K)	LUMENS (LM)	LENGTH (mm)	DIAM. (mm)	WEIGHT (KG)	BOX (cm)	CARTON QYT
CAN1	34PCS LED CANDLE CLEAR ES 3000K	E27	4=25	3000	260	105	Ø35	0.05	13x4x4	10/100
CAN2	34PCS LED CANDLE CLEAR BC 3000K	B22	4=25	3000	295	105	Ø35	0.05	13x4x4	10/100
CAN3	34PCS LED CANDLE CLEAR SES 3000K	E14	4=25	3000	260	110	Ø35	0.05	13x4x4	10/100
CAN4	34PCS LED CANDLE CLEAR SBC 3000K	B15	4=25	3000	260	110	Ø35	0.05	13x4x4	10/100
CAN5	34PCS LED CANDLE CLEAR ES 5000K	E27	4=25	5000	290	105	Ø35	0.05	13x4x4	10/100
CAN6	34PCS LED CANDLE CLEAR BC 5000K	B22	4=25	5000	290	105	Ø35	0.05	13x4x4	10/100
CAN7	34PCS LED CANDLE CLEAR SES 5000K	E14	4=25	5000	290	110	Ø35	0.05	13x4x4	10/100
CAN8	34PCS LED CANDLE CLEAR SBC 5000K	B15	4=25	5000	320	110	Ø35	0.05	13x4x4	10/100
CAN9	34PCS LED CANDLE FROSTED ES 3000K	E27	4=25	3000	280	105	Ø35	0.05	13x4x4	10/100
CAN10	34PCS LED CANDLE FROSTED BC 3000K	B22	4=25	3000	280	105	Ø35	0.05	13x4x4	10/100
CAN11	34PCS LED CANDLE FROSTED SES 3000K	E14	4=25	3000	280	110	Ø35	0.05	13x4x4	10/100
CAN12	34PCS LED CANDLE FROSTED SBC 3000K	B15	4=25	3000	280	110	Ø35	0.05	13x4x4	10/100
CAN13	34PCS LED CANDLE FROSTED ES 5000K	E27	4=25	5000	300	105	Ø35	0.05	13x4x4	10/100
CAN14	34PCS LED CANDLE FROSTED BC 5000K	B22	4=25	5000	300	105	Ø35	0.05	13x4x4	10/100
CAN15	34PCS LED CANDLE FROSTED SES 5000K	E14	4=25	5000	300	110	Ø35	0.05	13x4x4	10/100
CAN16	34PCS LED CANDLE FROSTED SBC 5000K	B15	4=25	5000	300	110	Ø35	0.05	13x4x4	10/100

UPDATED ON 05.02.2018