


## G4 LED GLOBE

- Input voltage: 12V AC/DC
  - Material: PC
  - Heatsink: ceramic
  - Diffuser: PC
  - LED chips: 18pcs SMD2835
  - CRI:  $\geq 80$
  - Power factor: 0.5
  - Ambient temperature:  $-10$  to  $35^{\circ}\text{C}$
  - Not suitable for dimming
  - Suitable for 2-way switching
  - Suitable for use with PIR sensor
- NB: external AC or DC control gear required



Part No.	Description	Base	Kelvin	Lumens	Watt	CRI	Dimensions	Box Weight	Box Dimensions	Carton QTY
G401	GLOBE LED 12V AC/DC G4	G4	3000K	160LM	1.5W	$\geq 80$	$\varnothing 14.8 \times 39.8 \text{mm}$	0.01kg	2x2x4cm	1/200

### Tested & Recommended Control Gears:

Brand	Part No.	Type	IP Rating
CLA	CLADR12W / CLADR12WFP	12W LED Driver (Constant Voltage)	IP20
CLA	DRIV1	12W LED Driver (Constant Voltage)	IP20
CLA	OTTER1	12W LED Driver (Constant Voltage)	IP67
CLA	CLA111011	10W LED Driver (Constant Voltage)	IP67
CLA	CLA113011	30W LED Driver (Constant Voltage)	IP67
CLA	CLA115011	50W LED Driver (Constant Voltage)	IP67
CLA	CLA1110011	100W LED Driver (Constant Voltage)	IP67
CLA	OTTER5	150W LED Driver (Constant Voltage)	IP67
CLA	CLA1120011	200W LED Driver (Constant Voltage)	IP67
CLA	OTTER7	300W LED Driver (Constant Voltage)	IP67
LUXMAN	ETH50.302VA	50W Transformer	IP65