


## GLS LED GLOBES

- Input voltage range: 176-264V AC 50/60Hz
- Material: PBT, aluminium, plastic & PC
- Diffuser: plastic
- LED chips: 2835 LED
- Power factor: ≥0.5
- Ambient temp: -15 to 40°C
- Not suitable for dimming
- Suitable for 2 way switching
- Suitable for use with sensors



Part No.	Description	Base	Kelvin	Lumens	Watt	CRI	Dimensions	Carton QTY
<b>6W MODELS</b>								
GLS13B	GLOBE LED ES GLS 6W 3000K FR	E27	3000K	470lm	6W	>80	Ø60x109mm	1/10/50
GLS14B	GLOBE LED ES GLS 6W 5000K FR	E27	5000K	490lm	6W	>80	Ø60x109mm	1/10/50
GLS15B	GLOBE LED BC GLS 6W 3000K FR	B22	3000K	470lm	6W	>80	Ø60x108mm	1/10/50
GLS16B	GLOBE LED BC GLS 6W 5000K FR	B22	5000K	490lm	6W	>80	Ø60x108mm	1/10/50
<b>8W MODELS</b>								
GLS18B	GLOBE LED ES GLS 8W 5000K FR	E27	5000K	630lm	8W	>80	Ø60x109mm	1/10/50
GLS19B	GLOBE LED BC GLS 8W 3000K FR	B22	3000K	600lm	8W	>80	Ø60x109mm	1/10/50
GLS20B	GLOBE LED BC GLS 8W 5000K FR	B22	5000K	630lm	8W	>80	Ø60x109mm	1/10/50
<b>13W MODELS</b>								
GLS21B	GLOBE LED ES GLS 13W 3000K FR	E27	3000K	1055lm	13W	>80	Ø60x110mm	1/10/50
GLS22B	GLOBE LED ES GLS 13W 5000K FR	E27	5000K	1107lm	13W	>80	Ø60x110mm	1/10/50
GLS23B	GLOBE LED BC GLS 13W 3000K FR	B22	3000K	1055lm	13W	>80	Ø60x110mm	1/10/50
GLS24B	GLOBE LED BC GLS 13W 5000K FR	B22	5000K	1107lm	13W	>80	Ø60x110mm	1/10/50
<b>15W MODELS</b>								
GLS25B	GLOBE LED BC GLS 15W 3000K FR	B22	3000K	1348lm	15W	>80	Ø60x117mm	1/10/50
GLS26B	GLOBE LED ES GLS 15W 3000K FR	E27	3000K	1348lm	15W	>80	Ø60x117mm	1/10/50
GLS27B	GLOBE LED BC GLS 15W 5000K FR	B22	5000K	1470lm	15W	>80	Ø60x117mm	1/10/50
GLS28B	GLOBE LED ES GLS 15W 5000K FR	E27	5000K	1470lm	15W	>80	Ø60x117mm	1/10/50