

Tel: 02 9938 7100 | Fax: 02 9938 7115

MR16 LED COLOURED GLOBES



Product Features:

Input voltage: 12V AC/DCHousing: plastic & aluminium

• Wattage: 5W (=30W incandescent)

• Power factor: 0.8

LED chips: 10pcs SMD2835
Ambient temperature: -10 to 40°C

Not suitable for dimming

• Suitable for 2-way switching

• Suitable for use with PIR sensor

NB: external AC or DC control gear required




















MR16B01A

MR16G01A

MR16R01A

Part No.	Description	Kelvin (K)	Lumens (LM)	Watt (W)	CRI	Weight (kg)	Box (cm)	Carton QTY
MR16B01A	GLOBE LED 12V AC/DC MR16 5W BLUE	BLUE	50	5=30	N/A	0.05	6x5x5	1/200
MR16G01A	GLOBE LED 12V AC/DC MR16 5W GREEN	GREEN	50	5=30	N/A	0.05	6x5x5	1/200
MR16R01A	GLOBE LED 12V AC/DC MR16 5W RED	RED	50	5=30	N/A	0.05	6x5x5	1/200

Tested & Recommended Control Gears for MR16 LED globes:

Brand	Part No.	Туре	IP Rating	
CLA	CLADR12W / CLADR12WFP	12W LED Driver (Constant Voltage)	IP20	
CLA	DRIV1	12W LED Driver (Constant Voltage)	IP20	
CLA	OTTER1	12W LED Driver (Constant Voltage)	IP67	
CLA	CLA111011	10W LED Driver (Constant Voltage)	IP67	
CLA	CLA113011	30W LED Driver (Constant Voltage)	IP67	
CLA	CLA115011	50W LED Driver (Constant Voltage)	IP67	
CLA	CLA1110011	100W LED Driver (Constant Voltage)	IP67	
CLA	OTTER5	150W LED Driver (Constant Voltage)	IP67	
CLA	CLA1120011	200W LED Driver (Constant Voltage)	IP67	
CLA	OTTER7	300W LED Driver (Constant Voltage)	IP67	
LUXMAN	ETH50.302VA	50W Transformer	IP65	