

SEC SERIES

Surface mounted **LED PAR30** Security Lights with / without sensor

General Lighting



SEC01



SEC01S (with sensor)

Fitting Features:

- Adjustable: up/down & side to side
- Input voltage: 200-240V AC
- Housing: PBT + PC
- E27 lamp holder
- Max.150W halogen PAR30 globes
- **10W LED PAR30 globes included**

Sensor Spec:

- Detection range: 180°
- Detection distance: 5-12m
- Detection motion speed: 0.6-1.5m/s
- Rated load: 1200W (HAL) 300W (CFL & LED)
- Time delay: Min: 10s±3s; Max: 10m±10m
- Ambient light: 3-2000 lux (adj)
- Ambient temp: -10 to 40°C
- Installation height: 1.8-2.5m
- Manual override via light switch



SEC02



SEC02S (with sensor)

IP44
Rated

3YEAR
Replacement
Warranty

Part No.	Description	GLOBE SPECIFICATION					WEIGHT (KG)	BOX (CM)	CARTON QTY	
		LED	KELVIN (K)	LUMENS (LM)	WATT (W)	CRI				BEAM ANGLE
SEC01	SECURITY PAR30 ES S/ADJ BLK without sensor	10PCS SMD 2835	5000	800	10	80	40°	0.4	22x11x11	40
SEC01S	SECURITY PAR30 ES S/ADJ BLK with sensor		5000	800	10	80	40°	0.55	25x15x11	32
SEC02	SECURITY PAR30 X 2 ES D/ADJ BLK without sensor		5000	2x800	2x10	80	40°	0.65	32x13x11	24
SEC02S	SECURITY PAR30 X 2 ES D/ADJ BLK with sensor		5000	2x800	2x10	80	40°	0.85	30x14x14	24

Globe Other Spec:

- Power factor: ≥0.5
- Suitable for 2-way switching
- Suitable for use with PIR sensor
- Life time: 30,000hrs
- IP rating: IP44
- Ambient temp: -10 to 40°C (The life of the lamp will gradually reduce if used outside these temperature parameters.)

