



NEW BACK SWITCH CHANGEABLE COLOUR TEMP/DOWNLIGHTS



PL9-TRI-60-G



PL10W-TRI



PL26-13-PR-02



AU22-DL15W/W/BS


Key Features



- Dimmable on Leading Edge, Trailing Edge, Universal 100%-3% also C-Bus & Dynalite Systems.
- Colour temperature changeable on back of downlight.
- IP44 Rated for indoors use and bathrooms.
- Frosted lens to decrease the glare.
- LED Chips SMD 2835, Power factor 0.95.
- IC-F or IC-4 certified; can be covered with normal building material without thermal risk.
- Flex in plug.

Applications

- Shopping Centres, Hotels, Restaurants, Homes, Show Rooms, etc.



PL26-13-PR-02

Product: **PL9-TRI-60-G**
PL10W-TRI
PL26-13-PR-02
AU22-DL15W/W/BS

Net Weight: 0.20/0.25/0.25/0.46kg
Outer ctn size: 495*420*260mm/480*360*310mm
Q'ty per ctn: 40/36/36/33 pcs
G.W per ctn: 11.10/11.50/12.90/18.10 kgs



DL28-10-PRE

Product: **DL28-10-PRE / DL28-10-PRE-S**

Net Weight: 0.21 kg
Outer ctn size: 510*365*270mm
Q'ty per ctn: 40 pcs
G.W per ctn: 11.50 kgs




DL28-10-PRE-S

Motion Sensor Downlight

Detection distance: 5-7m

Detection duration: Once detected, the light will stay on 100% brightness for 5 minutes, then it turns off.



TECHNICAL SPECIFICATIONS

Model.	LED Type	LED Q'ty (pcs)	Colour Temperature	Voltage (V)	Beam Angle	Wattage (W)	Luminosity (lm)	CRI(Ra)	Frame colour	Warranty	IP RATING	Dimmable	Driver
PL9-TRI-60-G	COB	1pc	3K 4K 5K	200~240v	60°	9W	750-850lm	80	White	3 years	IP44	Yes	External
PL10W-TRI	SMD2835	24pcs	3K 4K 5K	200~240v	120°	10W	900-950lm	80	White	3 years	IP44	Yes	External
PL26-13-PR-02	SMD2835	52pcs	3K 4K 5K	200~240v	90°	13W	1050-1150lm	80	White	3 years	IP44	Yes	External
AU22-DL15W/W/BS	SMD2835	64pcs	3K 4K 5K	200~240v	38°	15W	1200-1350lm	80	White	3 years	IP44	Yes	External
DL28-10-PRE	SMD2835	40pcs	3K 4K 5K	200~240v	120°	10W	850-950lm	80	White	3 years	IP44	Yes	Internal
DL28-10-PRE-S	SMD2835	40pcs	3K 4K 5K	200~240v	120°	10W	850-950lm	80	White	3 years	IP44	No	Internal