

DECO-13-RND-TRIO

















Fixed LED Downlight

Description

The DECO range of LED downlights have been designed with a deep-set frame to reduce glare from the light source. Featuring a wide light distribution, and with an ultra slim housing, allows for this downlight to be suitable for installations where ceiling space is minimal. Complete with a dimmable LED driver and flex and plug. Fully dimmable with suitable dimmers.

Now with TRIO, the added option of changing the colour temperature output of the downlight with a dip switch at the back of the fitting.







Specification Features

Input Voltage: 240 V AC
Power (W): 13W
IP rating (IP): 44*

 $Lumens \ (lm): \\ Warm \ White \ 3000 K-1186 lm$

Neutral White 4000K - 1306lm

White 5700K - 1237lm

LED type: SMD

CCT: 3000K - 4000K - 5700K (Switchable)

CRI: ≥83

Beam angle (°): 90°

Dimmable: Yes**

Lifespan (hrs): 50,000hrs

Cutout (∅): Ø90mm


IPart #: 01633D2-CSBMESH

* IP44 rating is from the underside of the down light once installed into the ceiling.

** Fully dimmable with suitable dimmers.

Trio Dip Switch Technology ww

Diagrams / Additional



Cutout: Ø90mm

	Item No.	Variant			CCT
		Wht	BLK	Alu	CCI
	DECO-13-RND	20420	20421	20422	
		DALI			TRIO
		21588	21589	21590	