

ies is in the ies is the ies is the ies is the ies is in the ies is it is is it is i

PLEX-VIVID IP67 Single Vivid Colour LED Strip



Description

The PLEX-VIVID series of LED strip incorporates the latest in LED COB chip technology, with true dotless appearance utilising 640 LEDs per metre. Operating on 24V DC allows for less resistive heat and longer run lengths. Choose from IP54 Indoor Strip including wet areas, or for waterproof installations, the IP67 Strip with silicon coating. Longer areas of weldless joints provide a more reliable solution avoiding breaks in continuity. Available in 15W per metre, which provides a bright and desirable light output for your desired area.

The PLEX-VIVID series comes with a choice of Vivid Red, Vivid Blue, Vivid Green or Vivid Yellow to complement your residential or commercial linear lighting project applications that require a vivid static colour within the four available colours. A comprehensive range of optional accessories including fast fix connectors, and L-joint connectors are available for complex installations. Ideal for kitchens, bathrooms, laundry, bars, restaurants, and all indoor highlighting applications.

Specification Features					
Colours:	Red, Blue, Green & Yellow				
Light Source:	COBLED				
Lumen Output:	Vivid Red - 89lm/m				
	Vivid Blue - 230lm/m				
	Vivid Green - 1400lm/m				
	Vivid Yellow - 1020lm/m				
Number of LED Per Metre:	640				
Wattage Per Metre:	15W				
Input Voltage:	24V DC				
Beam angle:	180°				
Wiring:	Parallel				
IP Rating:	IP67				
Cutting Increments/Sections:					
Requires:	24V DC Constant Voltage LED Driver				
Dimmable:	Yes**				
IES files:	Yes				
Continuous Run:	5m Max (one end driver feed)				
	10m (two end driver feed)				
* With the use of Domus drivers				Item No.	Variant CCT
* All LED strip must be installed on an aluminium heat sink, failure to do so WILL VOID WARRANTY. * * For dimming options please refer to the controller section for further details.					24140 Vivid Red
To amming options please rejer to the con					24141 Vivid Blue
				PLEX-VIVID-IP67	24142 Vivid Green
Diagrams / Additional					24143 Vivid Yellow
500mm	25mm Cutting Length	12mm Wide	16.5mm Wide (Er	nd Cap)	
+	Image: State	247+	247.0 (1) (2)		
	- <u>Å</u> <u>Å</u> -	- 4	-		
10mm	4.5mm High		10mm		
++			6	.5mm High (End Cap)	

Domus 29-31 Richland Street. Kingsgrove NSW 2208 | Phone: (02) 9554 9600 | email: enquiries@domuslighting.com.au Specification subject to change without prior notice.