

Tel: 02 9938 7100 | Fax: 02 9938 7115

IP65

**5 YEAR** 

REPLACEMENT

**WARRANTY** 

## **HIBTRI2**

**LED Power Switchable TRI-CCT** High Bay

## **Product Features:**

- Input voltage range: 120-277V AC 50Hz
- Constant current LED driver inbuilt
- Housing & Faceplate: powder coated Aluminium
- Heatsink: Aluminium
- Diffuser: Clear PC
- LED chips: 2835 LED
- CRI: >70
- Power factor: 0.95
- Flex & plug: 1.2m
- Ambient temp: -20 to 50°C
- Not suitable for dimming
- Suitable for 2-way switching
- Suitable for use with motion & microwave sensors
- Plug in PIR sensor for HIBTRI2 available (sold separetely)














Sensor

(Sold separately)

## TRI-POWER TRI-CCT ALL IN ONE



PART NO.			HIBTRI2
LUMENS	100W	3000K	16500LM
		4000K	17500LM
		5700K	17000LM
	150W	3000K	23250LM
		4000K	25500LM
		5700K	24000LM
	200W	3000K	30000LM
		4000K	32000LM
		5700K	31000LM
POWER FACTOR			0.95
DIMENSIONS			Ø350 X H175mm
BOX WEIGHT			3.6kg
BOX DIMENSIONS			370x370x145cm
CARTON QTY			1/1

	HIBSENSOR	
Sensor Type	PIR	
Wattage	<0.5W	
Installation Height	Recommended up to 12m	
Detection Angle	1200	
Time Delay	5s / 1min / 5min / 10min	
Ambient Temperature	-20 to 60°C	
Stand by Dim Level Setup	0%, 10%, 20%, 30%	
UV Resistant	Yes	
Ambient Light	day and night	
Shi Town of the Company of the Compa	ModelMDDVR-PH-Z	

<sup>\*</sup>Must be installed by a licenced electrician (Installation instructions sheet provided in each product box)